

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

5105 and 5205 Series Tractors



HYDRAULIC

FILTER ELEMENT (5105, 5205) – [RE45864](#)

Replace after 100 and 250 hours, and then every 1200 hours and as required.

(Click here for [capacity](#))

ENGINE

OIL FILTER (5105, 5205)– [T19044](#) (Export)

Replace after 100 and 250 hours, and then after every 250 hours or every year.

(Click here for [capacity](#))

ENGINE

FINAL FUEL FILTER (5105, 5205) – [RE60021](#)

Replace every 500 hours and as required.

ENGINE

SECONDARY AIR FILTER (5105, 5205) – [RE68049](#)

PRIMARY AIR FILTER (5105, 5205) – [RE68048](#)

Replace every year.



JOHN DEERE

Genuine Parts and Service

CAPACITIES

5105 and 5205 Series Tractors

CAPACITIES (Approximate):

Fuel Tank:

5105 and 5205 Series Tractors 84.8 L (22.4 gal)

Crankcase including Filter Change:

5105 and 5205 Series Tractors 7.5 L (1.98 gal)

Cooling System:

5105 and 5205 Series Tractors 9.5 L (2.5 gal)

SyncReverser™ Transmission:

Grease Axle 32 L (8.4 gal)

Oil Axle 32 L (8.4 gal)

Mechanical Front Wheel Drive (MFWD) - If Equipped:

Wheel Hubs (Each) 0.7 L (0.18 gal)

Axle Housing 4.5 L (1.19 gal)

[Return to Filter Overview](#)

