

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

800 Series 850 (16001-), 900 Series 950 (20001-), 50 Series 1050 (11001-) Tractors

ENGINE

PRIMARY AIR FILTER

[M800354](#) (1050)

[MIU804763](#) (850, 950)

SECONDARY FUEL FILTER

[MIU800643](#) (all)

Change as required.

ENGINE

OIL FILTER

[M801002](#) (all)

Change after first 50 hours then every 200 hours or annually once, which ever comes first.

(Click here for [capacity](#))

HYDRAULIC

OIL FILTER – [RE27284](#) (all)

Replace after first 100 hours then every 200 hours.

(Click here for [capacity](#))

ENGINE

PRIMARY AIR FILTER

[CH12767](#) (all)

SECONDARY AIR FILTER

[CH12881](#) (all)

Service after every 200 hours.
Replace annually once.



JOHN DEERE

Genuine Parts and Service

https://www.deere.com/en_US/parts/parts_by_industry/ag/fmi/filter_maintenance_information.page

CAPACITIES

800 Series 850 (16001-), 900 Series 950 (20001-), 50 Series 1050 (11001-) Tractors

CAPACITIES (Approximate):

Fuel Tank:

850, 950	32 L (8.5 gal)
1050	42 L (11 gal)

Cooling System:

Cool-Gard™ II

850	5.5 L (1.2 gal)
950	6 L (1.31 gal)
1050	6.2 L (1.36 gal)

Crankcase with Filter:

Plus-50 II™

850	4.5 L (0.98 gal)
950, 1050	6.4 L (1.4 gal)

Transmission and Hydraulic System:

Hy-Gard™

.....	26 L (5.71 gal)
-------	-----------------

Mechanical Front Wheel Drive (MFWD) Axle:

Hy-Gard™

Axle Housing

850.....	6.5 L (1.42 gal)
950, 1050.....	8.5 L (1.86 gal)

[Return to Filter Overview](#)

