

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

4940 Self-Propelled Sprayer

CAB

AIR FILTER RECIRCULATION ACTIVATED CARBON – [RE199682](#)

Replace filter every 500 hours or annually, DO NOT clean filter. Replace filter at service interval or when performance indicates.



ON BOARD AIR (OBA)

AIR DRYER CARTRIDGE – [AN204967](#)


Replace annually.



ENGINE

DIESEL PARTICULATE FILTER (DPF) – [RE542183](#)

Service as indicated by display. See your John Deere dealer or qualified service provider.



ENGINE

FUEL FILTER KIT – [RE525523](#) (W/ENGINE 6090 HN006)

PRIMARY FUEL FILTER – [RE539465](#) SECONDARY FUEL FILTER – [RE533910](#) (W/ENGINE 6090 HN004)

Replace every 500 engine hours.



CAB

AIR FILTER ACTIVATED CARBON – [RE199681](#)

Replace every 500 engine hours or annually.



HYDROSTATIC DRIVE OIL FILTER – [AT314164](#)

Replace every 500 engine hours.
(Click here for [capacity](#))



ENGINE

SECONDARY AIR FILTER – [RE210103](#)

Do not attempt to clean secondary filter. Replace secondary filter every second filter change of primary filter. Install new secondary filter immediately to prevent dust from entering air intake system.



HYDRAULICS

OIL FILTER – [AH128449](#) HYDRAULIC RESERVOIR FILTER – [AN207572](#)

Replace Oil Filter every 500 engine hours.
(Click here for [capacity](#))



ENGINE

PRIMARY AIR FILTER – [RE210102](#)

Replace filters at least once a year or six cleanings, or if air filter indicator remains ON.



ENGINE

OIL FILTER – [RE509672](#)

Initial Oil Filter change is at 100 engine hours; then every 500 engine hours thereafter.

Refer to the OM for information regarding drain intervals. If PLUS-50™ II engine oil and a John Deere™ filter are used.

(Click here for [capacity](#))



JOHN DEERE

Genuine Parts and Service

CAPACITIES

4940 Self-Propelled Sprayer

CAPACITIES (Approximate):

Fuel Tank:

Use **ULSD Fuel Only**

..... 568 L (150 gal)

Cooling System with Heater:

Cool-Gard™ II

..... 41 L (10.8 gal)

Crankcase including Filter:

Plus-50™ II

..... 31 L (8.2 gal)

Hydraulic Reservoir:

Turf-Gard™ or TORQ-GARD SUPREME™ 10W-30

..... 83 L (22 gal)

Hydraulic System:

Turf-Gard™ or TORQ-GARD SUPREME™ 10W-30

Hydraulic and Hydrostatic..... 163 L (43 gal)

Final Drives (Front Hubs) Each:

GL-5

..... 3.8 L (1 gal)

Final Drives (Rear Hubs) Each:

GL-5

..... 3.8 L (1 gal)

[Return to Filter Overview](#)

*For complete recommended fluid specifications please refer to the current Operations Manual.

