

REPLACEMENT PARTS GUIDE

5105 Tractor (TREM IIIA Engine) (India Edition)



HYDRAULIC



FILTER
[RE45864](#) OIL FILTER

Replace after every 500 hours and every 1250 hours.

ENGINE



OIL FILTER
[RE507204](#) (FOR INDIA)
[T19044](#) (FOR EXPORT)

Change every 250 hours and 500 hours.



AIR FILTER
[RE68048](#) PRIMARY AIR FILTER
[RE68049](#) SECONDARY AIR FILTER

Change after every 250 hours or annually which ever comes first.



PRIMARY FUEL FILTER
[RE508953](#) PRIMARY FUEL FILTER
[RE508954](#) FINAL FUEL FILTER

Replace after every 250 hours and as required.

CAPACITIES

5105 Tractor (TREM IIIA Engine) (India Edition)

CAPACITIES (Approximate):

Fuel Tank:

.....60 L (13.2 gal)

Crankcase including Filter Change:

Plus-50™ II

.....7.5 L (1.98 gal)

Cooling System:

Plus-50™ II

5105 and 5205 Series Tractors.....9.8 L (2.59 gal)

Transmission and Hydraulic System:

Hy-Gard™

(4WD).....32 L (7.03 gal)

(2WD).....31.4 L (6.90 gal)

Mechanical Front Wheel Drive (MFWD) Axle Housing:

MFWD Axle Oil

Hy-Gard™

.....5.9 L (1.29 gal)

REPLACEMENT PARTS GUIDE

5105 Tractor (TREM IIIA Engine) (India Edition)

ENGINE



BRAKE DISK
[SJ18395](#)
[SJ18396](#) (PLANETARY)



CLUTCH DISK
[SJ29350](#)
[RE242274](#) (PTO)
[SJ23064](#) (SINGLE)
[SJ41472](#)



BATTERY
[RE251537](#)



ALTERNATOR
[RE258846](#) (AUTOLEK)



FAN DRIVE BELT
[SU63793](#) (LGTH = 1340 mm)



CAB



SEAT
[SJ18028](#) (BELT)
[SJ18041](#) (BOTTOM)
[SJ26883](#) (BELT)
[RE212691](#) (ROPS)
[SJ34660](#) (BELT)
[RE73192](#) (BELT)

AXLE



TIE ROD
[RE190506](#) (RH)
[RE190481](#) (LH)
[SJ14021](#) (MFWD)
[R141317](#) (SCV)(MITA)
[RE216708](#) (SCV)(MITA)
[R225906](#) (SCV)