


FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

W260 Windrower

CAB

FRESH AIR FILTER – [RE284091](#)

Clean after every 50 hours and replace as required.



CAB

RECIRCULATION AIR FILTER – [L214634](#)

Clean after first 100 hours and every 250 hours thereafter or each season whichever occurs first and replace as required.



ENGINE

DIESEL PARTICULATE FILTER

[RE561836](#) - 6068HE002

[DZ100484](#) - 6068HE054 and 6068HE056

Replace after every 5500 hours and as required.

Note:-When exhaust filter and warning light indicators are alerted on display replace within 250 hours.



ENGINE

FUEL TANK VENT FILTER [H216169](#)

Clean after every 500 hours or each season whichever occurs first.



ENGINE

DIESEL EXHAUST FLUID (DEF) DOSING UNIT FILTER

[RE554498](#) USE FOR [DZ119474](#) (DOSING UNIT PUMP).

[DZ114640](#) USE FOR [RE552175](#) OR [DZ111283](#) (DOSING UNIT PUMP).

Replace after every 4500 hours or 3 years whichever occurs first.

ENGINE

CRANKCASE BREATHER FILTER – [RE553703](#)

Replace after every 1500 hours.



ENGINE

PRIMARY AIR FILTER – [AN403918](#)

Replace as required or each season, whichever occurs first.

SECONDARY AIR FILTER – [AN403919](#)

Replace as required or each season, whichever occurs first.



ENGINE

OIL FILTER – [RE539279](#)

Replace after first 100 hours, then every 250 hours or each season, whichever occurs first. If Plus-50™ oil is used along with John Deere™ oil filter, the oil interval may be extended by 250 hours.

(Click here for [capacity](#))



ENGINE

DIESEL EXHAUST FLUID (DEF) TANK VENT FILTER [H216169](#)

Clean after every 500 hours or 1 year whichever occurs first.



HYDRAULIC

HYDROSTAT FILTER

[AH128449](#) (-420000)

[T175002](#) (420001-)

Replace after every 400 hours or each season, whichever occurs first.

(Click here for [capacity](#))



HYDRAULIC

RESERVOIR VENT FILTER – [AT101565](#)

Replace after every 400 hours or each season, whichever occurs first.

(Click here for [capacity](#))



ENGINE

FUEL FILTER KIT (Includes Primary and Secondary)

[RE556406](#) (Engine Option Code 35D5)

PRIMARY FUEL FILTER

[DZ115391](#) (Engine Option Code 35JL, 35K3)

SECONDARY FUEL FILTER

[DZ115392](#) (Engine Option Code 35JL, 35K3)

Replace after every 500 hours or each season, whichever occurs first.



JOHN DEERE

Genuine Parts and Service

https://www.deere.com/en_US/parts/parts_by_industry/ag/fmi/filter_maintenance_information_page

CAPACITIES

W260 Windrower

CAPACITIES (Approximate):

Fuel Tank:
Diesel Fuel

..... 586 L (155 gal)

Cooling System:
Cool-Gard™ II

..... 56.78 L (15 gal)

Engine Oil with Filter:
Plus-50™

..... 31.4 L (8.30 gal)

Hydraulic System (Reservoir):
Hy-Gard™

..... 95 L (25 gal)

Hydraulic System (Total):
Hy-Gard™

..... 143.8 L (38 gal)

Diesel Exhaust Fluid (DEF) Tank:

John Deere™ Diesel Exhaust Fluid

..... 24 L (6.34 gal)

Final Drives Each:
GL-5

..... 3.8 L (1 gal)

Pump Drive Gear Case:
Hy-Gard™

..... 3.8 L (1 gal)

Pump Drive Gear Case: (Including Cooling Loop)
Hy-Gard™

..... 5.7 L (1.6 gal)

[Return to Filter Overview](#)

