

## 755 CRAWLER LOADER

32,005 lb (14 517 kg)

Transport Height.....10 ft 2.6 in. (3.11 m)

Transport Length.....17 ft 9 in. (5.41 m)

Machine Width .....10 ft (3.05 m)

### ENGINE .....John Deere 300 Series

Number of Cylinders and Displacement .....6 cylinders, 414 cu in. (6.8 L)

Air Intake System.....Turbocharged

Bore and Stroke .....4.19 x 5 in. (106 x 127 mm)

Net hp at 2100 rpm.....110 SAE hp (82 kW) DIN 82 kW

Maximum Torque at 1300 rpm.....400 lb-ft (542 N·m)

Nozzle Opening Pressure:

New .....3700 + 50 psi (25 510 + 345 kPa)

Used .....3500 + 50 psi (24 135 + 345 kPa)

Valve Clearance (Cold):

Intake.....0.014 in. (0.36 mm)

Exhaust .....0.018 in. (0.46 mm)

Oil Pressure at Fast Idle .....50 ± 15 psi (345 ± 105 kPa)

Static Injection Pump Timing .....Timing lines aligned w/flywheel located at TDC

Dynamic Injection Pump Timing at Rated Load rpm\* .....15 + 0 - 1° BTDC

Speeds:

Slow Idle, Disconnect Clutch Engaged.....975—1000 rpm

Fast Idle, Disconnect Clutch Engaged .....2275—2300 rpm

Rated Full Load .....2100 rpm

Cylinder Pressure Hot (Min) .....350 psi (2415 kPa) cranking with injectors removed

Turbo Boost Pressure at Rated Full Load .....9—12 psi (62—83 kPa)

Flywheel Teeth.....129

Note: \*For latest information, see Dealer Technical Assistance Center (DTAC) Solution K000413.

### TRANSMISSION

Model and Speeds .....Hydrostatic: variable speed, forward and reverse

Charge Pressure in Neutral .....260—340 psi (1795—2345 kPa)

High Pressure Relief (in Forward and Reverse) .....6100—6500 psi (42 060—44 820 kPa)

Oil Cooler Bypass Valve .....40 psi (280 kPa)

Maximum Engine rpm Pulldown .....1800 rpm

### HYDRAULIC SYSTEM—Open-Center

Pump Size .....6.88 cu in. (112.7 cm<sup>3</sup>)

Pump Flow (Min):

New .....54 gpm (204.7 L/min) at 2500 psi  
(17 240 kPa) and 2100 rpm

Used .....49.5 gpm (187.6 L/min) at 2500 psi  
(17 240 kPa) and 2300 rpm

### RELIEF VALVE SETTINGS

System Relief Valve .....2500 + 175 - 0 psi (17 240 + 1210 - 0 kPa)

Circuit Relief Valve:

Bucket Dump .....3000 + 225 - 0 psi (20 685 + 1550 - 0 kPa)

Bucket Rollback .....3000 + 225 - 0 psi (20 685 + 1550 - 0 kPa)

Boom Lift .....3000 + 225 - 0 psi (20 685 + 1550 - 0 kPa)

Auxiliary .....3000 + 225 - 0 psi (20 685 + 1550 - 0 kPa)

## CYCLE TIMES (At Fast Idle and Hot Oil)

Boom Raise .....	5.0 sec
Bucket Dump .....	1.3 sec
Boom Lower (Float) .....	3.2 sec

## LUBRICANTS

See front of this book for the codes [ ].

<b>CAPACITIES</b>	<b>U.S.</b>	<b>Imp.</b>	<b>Metric</b>
Engine:			
Cooling System [N] .....	7 gal	5.8 gal	26.5 L
Crankcase w/ Filter [E].....	20 qt	16.7 qt	18.9 L
Final Drive (Each):			
1st Reduction [J] .....	5.4 gal	5.2 gal	20.3 L
2nd Reduction [J] .....	3.5 gal	2.9 gal	13.2 L
Fuel Tank .....	73 gal	60.8 gal	276.3 L
Hydraulic System [C] .....	37 gal	30.8 gal	140.1 L
Hydrostatic Drives [L].....	33 gal	27.5 gal	124.9 L
Splitter [M].....	1.5 gal	1.3 gal	5.7 L