

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

7425 and 7525 Tractors

ENGINE

PRIMARY AIR FILTER
[AL172781](#)

SECONDARY AIR FILTER
[AL150288](#)


Replace after every 1500 hours or 2 years (whichever comes first) or after 5 cleanings of the primary element. change as required.



CAB

AIR FILTER
[AL225552](#)

Change as required.



ENGINE

OIL FILTER
[RE504836](#)

Change after first 100 hours then after every 250 hours using API-CI oil. If the sulfur level exceeds 0.7%, reduce the service interval by 50%.

(Click here for [capacity](#))



ENGINE

PRIMARY FUEL FILTER
[RE515335](#)

SECONDARY FUEL FILTER
[RE62419](#)

Replace every 250 hours.



ENGINE

OIL FILTER
[AL169573](#)

Replace after first 100 hours then after 500 hours.

(Click here for [capacity](#))



HYDRAULIC

OIL FILTER
[AL221066](#)
[AL156624](#)

Replace after first 100 hours then after 500 hours.

(Click here for [capacity](#))



http://www.deere.com/en_US/parts/service/support/filter/overviews

CAPACITIES

7425 and 7525 Tractors

CAPACITIES (Approximate):

Fuel Tank:

7425.....	207 L (54.7 gal)
7525.....	250 L (66 gal)

Cooling System:

Cool-Gard™ II

.....	20 L (5.28 gal)
-------	-----------------

Crankcase with Filter:

Plus-50™ II

.....	19.5 L (5.2 gal)
-------	------------------

Transmission/Hydraulics:

Hy-Gard™

PowrQuad Transmission	77 L (20.3 gal)
Extra With Creeper Transmission.....	1 L (0.3 gal)
Extra With Front-Wheel Drive.....	3 L (0.8 gal)

Mechanical Front Wheel Drive (MFWD) Axle Housing:

Hy-Gard™

7425 (APL/AS 2045).....	6.6 L (1.7 gal)
7525 (APL/AS 2060).....	7.0 L (1.8 gal)
7525 (045JD).....	9.5 L (2.5 gal)
7525 (045JDS20)	10.6 L (2.8 gal)

Mechanical Front Wheel Drive (MFWD) Hubs (Each):

Hy-Gard™

7425 (APL/AS 2045).....	0.8 L (0.2 gal)
7525 (APL/AS 2060).....	1.7 L (0.4 gal)
7525 (045JD).....	2 L (0.5 gal)
7525 (045JDS20)	2 L (0.5 gal)

[Return to Filter Overview](#)

