

REPLACEMENT PARTS GUIDE

5C Tractors - 5036C and 5042C (Export)

ENGINE



PRIMARY AIR FILTER
[RE68048](#)
SECONDARY AIR FILTER
[RE68049](#)
Replace every 250 hours and annually.



FINAL FUEL FILTER
[RE539502](#)
Replace every 750 hours.



OIL FILTER
[RE507204](#) (FOR INDIA)
[T19044](#) (FOR EXPORT)
Replace initially after 100 hours and every 250 hours.



TRANSMISSION



HYDRAULIC FILTER
[RE280728](#)
Replace initially after 100 hours, every 500 hours and every 2000 hours.

CAPACITIES

5C Tractors - 5036C and 5042C (Export)

CAPACITIES (Approximate):

Fuel Tank:

..... 45 L (11.9 gal)

Cooling System:

Cool-Gard™ II

..... 9 L (2.24 gal)

Transmission and Hydraulic System:

Hy-Gard™

5032C 27 L (7.13 gal)

5042C 26 L (6.87 gal)

REPLACEMENT PARTS GUIDE

5C Tractors - 5036C and 5042C (Export)

ENGINE



BRAKE DISK
[SJ23437](#)



CLUTCH DISK
[SU32910](#)



ALTERNATOR
[RE258846](#)



FAN BELT DRIVE
[SU63793](#)



CAB



SEAT
[SJ12392](#)

AXLE



TIE ROD
[RE275353](#)
(POWER STEERING)
[RE282064](#)
(2WD)