

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

5M Series (Tier 3) Tractors - 5085M, 5095M, 5105M (Worldwide Edition) and 5095MH, 5105ML (North America Edition)

CAB

RECIRCULATION AIR FILTER -
[RE195491](#)
(5085M, 5095M, 5095MH, 5105M)
Service Annually.



CAB

FRESH AIR FILTER
[RE198488](#)
(5085M, 5095M, 5095MH, 5105M)
Service Annually.



ENGINE

PRIMARY AIR FILTER
[AL172780](#) W/ ASPIRATOR
(Applicable to all models)
(5095M) - [RE253518](#)

SECONDARY AIR FILTER
[AL150288](#) W/ ASPIRATOR
(Applicable to all models)
(5095M) - [RE253519](#)

Service after every 1200 hours.



ENGINE

PRIMARY FUEL FILTER
[RE541922](#)
FINAL FUEL FILTER
[RE526557](#)

Replace after 500 hours.



HYDRAULIC

OIL FILTER - [SJ11784](#)

Replace after every 600 hours.



ENGINE

OIL FILTER
[RE504836](#)

Replace initially after 300 hours and after every 300 hours (When not using John Deere Plus-50™ oil and filter). Replace after every 500 hours (When using John Deere Plus-50™ oil and filter).



http://www.deere.com/en_US/parts/service/support/filter/overviews

CAPACITIES

5M Series (Tier 3) Tractors - 5085M, 5095M, 5105M (Worldwide Edition) and 5095MH, 5105ML (North America Edition)

CAPACITIES (Approximate):

Fuel Tank:

5085M, 5095M, 5095MH, 5105M

Cab 154 L (40.7 gal)

5085M, 5095M, 5095MH, 5105M, 5105ML

OOS 115 L (30.3 gal)

Cooling System:

Cool-Gard™ II

Cab 15.5 L (4 gal)

OOS 13.5 L (3.6 gal)

Crankcase W/ Filter:

..... 13 L (3.4 gal)

Transmission and Hydraulic System:

Hy-Gard™

SyncShuttle Plus™ transmission 53 L (14 gal)

PowrReverser Plus™ Transmission 53 L (14 gal)

PowrReverser™ or SyncReverser™

Transmission 53 L (14 gal)

MECHANICAL FRONT-WHEEL DRIVE (MFWD) AXLE:

Differential Housing 5 L (1.32 gal)

Wheel Hub (Each) 0.8 L (0.21 gal)

[Return to Filter Overview](#)

